



IFW

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

APPLICANT: Graham Anthony Inchley **GROUP:** 3618
SERIAL NO: 10/767,639 **EXAMINER:** Unknown
FILED: January 29, 2004
FOR: TRUCKS FOR SKATEBOARDS

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313

Sir:

TRANSMITTAL OF CERTIFIED COPY

Attached please find the certified copy of the foreign application from which priority is claimed for this case:

Country: United Kingdom
Appln No.: 0302143.3
Filing Date: January 30, 2003

Respectfully submitted,

Arlene J. Powers
Registration No. 35,985
Gauthier & Connors LLP
225 Franklin Street
Boston, Massachusetts 02110
Telephone: (617) 426-9180
Extension 110

I hereby certify that this paper (along with any paper referred to as being attached or enclosed) is being deposited with the United States Postal Service on the date shown below with sufficient postage as first class mail in an envelope addressed to the: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

Sarah Kennedy

6/30/04

Date



THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE


The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

Dated

R. Hobney
16 February 2004

THIS PAGE BLANK (USPTO)



30JAN03 E781124-1 C23542
P01/7700 0.00-0302143.3

THE PATENT OFFICE

30 JAN 2003

NEWPORT

The Patent Office

Cardiff Road
Newport
South Wales
NP10 8QQ

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

1. Your reference

B 1043

2. Patent application number

(The Patent Office will fill in this part)

0302143.3

30 JAN 2003

3. Full name, address and postcode of the or of each applicant (underline all surnames)

GRAHAM ANTHONY
INCHLEY, 7 Marks Road,
Borley, SOUTHAMPTON,
SO30 2EY.

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

085549 33001

4. Title of the invention

TRUCKS FOR SKATEBOARDS.

5. Name of your agent (if you have one)

J. A. BOUTLAND.

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

J. A. BOUTLAND, Chartered Patent
Agent,
8, HEATHERSTONE AVENUE,
DIBDEN PURLIEU, SOUTHAMPTON,
SO45 4LQ

Patents ADP number (if you know it)

22812002

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)

Date of filing
(day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day / month / year)

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

NO.

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description

Claim(s)

Abstract

Drawing(s)

4
2
1
4

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77)

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

J. A. Boutland

Date 29.1.2003

12. Name and daytime telephone number of person to contact in the United Kingdom

J. A. BOUTLAND, Chartered Patent Agent
023 - 80 - 843749.

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 08459 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

TRUCKS FOR SKATEBOARDS

This invention relates primarily, but not exclusively, to trucks for skateboards, although as used herein, the term "truck" relates to steering devices for means of transport other than skateboards. For example, roller-skates, or other devices that use a two-bogey, four-wheel, "lean to steer" method of changing direction.

The invention provides a truck for a skateboard which enables a substantial degree of positive steering and requires less material to manufacture than a conventional truck so as to enable a skateboarder to improve his performance.

According to the invention, a truck for a skateboard comprises a base structure for attachment to the skateboard deck, a yoke assembly having spaced-apart portions flexibly located by the base structure, and a king-pin assembly including a king-pin for clamping the base structure and the yoke assembly together, so that with a pair of skateboard wheels carried by the truck, the arrangement is such that the rotational axis of the wheels is disposed substantially at right angles to the longitudinal axis of the king-pin and said rotational axis is also disposed at a steering head angle of between 45° and 20° to the vertical when the skateboard is at rest, on the ground.

The steering head angle is preferably at substantially 30° to the vertical.

The king-pin assembly is preferably disposed between the spaced-apart portions flexibly located by the base structure.

An embodiment of the invention will now be described by way of example only, with reference to the accompanying drawings, wherein:-

Figure 1 is a side view in medial section of a truck for a skateboard,

Figure 2 is an inverted view of the base structure thereof,

Figure 3 is an end view in the direction of arrow A of Figure 2,

Figure 4 is an end view of the yoke assembly,

Figure 5 is a side view of the yoke assembly, and Figures 6, 7 and 8 and Figures 9, 10 and 11 illustrate details of bushes that may be employed by the yoke assembly.

5 With particular reference to Figure 1, a truck 1 for a skateboard 2 comprises a base structure 3 detachably secured to the underside 30 of the skateboard deck 4, a yoke assembly 17 having spaced-apart (upper and lower) portions 17a, 17b flexibly located by the base structure 3, and a king-pin assembly 5 including a king-pin 7 for clamping the base structure 3 and the yoke assembly 17 together.

10 The arrangement is such that with a pair of skateboard wheels 6 carried by the truck 1, the rotational axis 8 of the wheels 6 is disposed substantially at right angles to the longitudinal axis 9 of the king-pin 7 and said axis rotational 8 is also disposed at a steering head angle α of substantially 30° to the vertical, (represented by vertical line 10), when the skateboard is at rest on the ground, i.e. in the position shown. The steering head axis is represented by line 31.

15 The longitudinal axis 9 of the king-pin 7 extends between the flexibly-located upper and lower portions 17a, 17b. This placement of the king-pin 7 assists control of the skateboard 2.

20 The base structure 3 has a flanged portion 14 defining a flat surface 15. The portion 14 is releasably clamped to the underside of the skateboard deck 4 by four nut and bolt assemblies, (not shown), located by drilled holes 16 (Figure 2).

25 Ground level is indicated by reference numeral 24.

30 The yoke assembly 17 carries the king-pin assembly 5, the king-pin 7 of which is located by axially-spaced bushes 18, 18a of resilient plastics material, such as polyurethane. The bushes 18, 18a are separated by an inwardly disposed flange portion 33 of the yoke assembly 17. The king-pin 7 has a button shaped head 7a and is releasably secured in place by a locknut 19. The base structure 20 has a lower, spherical end 20a which is

received by a cooperating bearing 21 of resilient polyurethane located by a concave hollow 34 formed in the lower yoke portion 17b.

5 The axis 8 of the wheels 6 is defined by a pair of hollow stub axles 22 (Figure 4) upon which the wheels are mounted. The stub axles 22, which are of steel, are located by the lower end 17b of the yoke portion 17, and are disposed well below the king-pin assembly 5. The arrangement reduces weight.

10 The upper end 17a of the yoke portion 17 is of part spherical form and is located by a cooperating bearing 23 of resilient polyurethane. The bearing 23 comprises a plug secured in the base structure 3.

15 The skateboard 2 is conveniently provided with two trucks 1 mounted on the skateboard deck 4 in tandem. Each truck is a mirror image of the other. As the skateboard deck 4 is tilted towards the intended change in direction, the yoke assemblies 17 rotate about their steering head axis 31. Tilting the skateboard deck 4 to the left for example, causes the front and rear outer wheels 6 to move apart, and the front and rear inner wheels 6 to move together, resulting in the intended change of direction.

20 When pressure is released from the skateboard deck 4, the yoke portions 17 are returned to their central positions by resilience in the bushes 18, and 18a. The steering head angle of each truck 1 remains substantially constant during manoeuvres.

25 The material of both the base structure 3 and yoke assembly 17 of each truck 1 is preferably of T6 spec aluminium alloy or titanium. The king-pin 7, which preferably is of high tensile steel, acts as a locking device to prevent the yoke portion 17 separating from the base structure 20. The yoke portion 17 is disposed between the bushes 18, 18a so that a substantially uniform compression force, (adjustable, depending on the skateboard rider's weight), is imparted. This compressive force keeps the yoke portion 30 17 in a substantially central position. The bushes 18, 18a also assist in locking (clamping) the yoke portion 17 to the base structure 20 bearings.

The bushes 18, 18a can be changed to suit requirements. For example, salom, downhill speed racing or bowl riding.

5 The yoke portion 17 supports the associated wheel stub axles 22 which in turn supports the wheels 6 and their bearings. As steering inputs are made, the yoke portion 17 pivots about the base plate 20 and a change in direction occurs. The width of the yoke portion 17 can be changed to suit requirements.

10 To reduce weight, up to an inner one third of stub axle material could be removed.

The upper and lower bearings 23, 21 serve as shock absorbers and ensure a good fit between the yoke portion 17 and base structure 20.

15 In the modified yoke assembly illustrated by Figure 5, the bearing 21 is held in place by a plug 34 secured in the lower portion 17b of the yoke assembly 17. Figures 6, 7 and 8 illustrate alternative upper bushes 18. The bush 18 of Figure 8 has a frusto-conical profile.

20 Figures 9, 10 and 11 similarly illustrate alternative lower bushes 18a. The bush 18a of Figure 9 has a chamfered edge.

The shapes of the bushes 18a aid assembly and disassembly of a truck 1, as they then avoid interference with adjacent parts of the truck.

25 As mentioned above, the steering head angle α may be between 45° and 20° to the vertical. However, an angle of substantially 30° to the vertical is preferred.

30 It will be appreciated that a truck according to the invention has application other than to a truck for a skateboard. For example, roller-skates or other devices that use a two-bogey, four wheel, lean to "steer" method of changing direction.

CLAIMS

1. A truck for a skateboard comprising a base structure for attachment to the skateboard deck, a yoke assembly having spaced-apart portions flexibly located by the base structure, and a king-pin assembly including a king-pin for clamping the base structure and the yoke assembly together, so that with a pair of skateboard wheels carried by the truck, the arrangement is such that the rotational axis of the wheels is disposed substantially at right angles to the longitudinal axis of the king-pin and said axis is also disposed at a steering head angle of between 45° and 20° to the vertical when the skateboard is at rest on the ground.
2. A truck as claimed in Claim 1, wherein the steering head angle is substantially 30° to the vertical.
3. A truck as claimed in Claim 1 or 2, wherein the longitudinal axis of the king-pin extends between the spaced apart portions flexibly located by the base structure.
4. A truck as claimed in Claim 1, 2 or 3, wherein the king-pin is located by a pair of axially-spaced bushes of resilient material carried by the yoke assembly.
5. A truck as claimed in Claim 4, wherein the bushes are separated by an inwardly disposed flange portion of the yoke assembly.
6. A truck as claimed in Claim 4 or 5, wherein one bush is of frusto-conical form.
7. A truck as claimed in any one of Claims 4, 5, or 6, wherein one bush has a chamfered edge.
8. A truck as claimed in any one of Claims 4 to 7, wherein resilient material of the bushes is polyurethane.

9. A truck as claimed in any one of Claims 1 to 8, wherein one spaced-apart portion of the yoke assembly is of part-spherical form.

5 10. A truck as claimed in Claim 9, wherein the part-spherical portion of the yoke assembly is located by a co-operating bearing of resilient material.

11. A truck as claimed in Claim 10, wherein the co-operating bearing is of polyurethane.

10 12. A truck as claimed in anyone of Claims 8 to 11, wherein the other spaced-apart portion of the yoke assembly is formed with a concave hollow which locates a bearing of resilient material which receives a spherical part of the base structure.

13. A truck as claimed in Claim 12, wherein said bearing is of polyurethane.

15

14. A truck substantially as herein before described, with reference to Figures 1 to 4 of the accompanying drawings.

20

15. A truck as claimed in Claim 14, modified substantially as herein before described, with reference to Figures 5, or 6, 7 and 8, or 9, 10 and 11 of said drawings.

16. A skateboard provided with a pair of trucks each as claimed in any one of Claims 1 to 15.

ABSTRACT


With reference to Figure 1, a truck 1 for a skateboard 2 comprises a base structure 3 detachably secured to the underside 30 of the skateboard deck 4, a yoke assembly 17 having spaced-apart upper and lower portions 17a, 17b flexibly located by the base structure 3, a king-pin assembly 5 including a king-pin 7 for clamping the base structure 3 and the yoke assembly 17 together, and a pair of skateboard wheels 6 carried by the truck 1.

The arrangement is such that the rotational axis 8 of the wheels 6 is disposed substantially at right angles to the longitudinal axis 9 of the king-pin 7 and said axis 8 is also disposed at a steering head angle of substantially 30° to the vertical, (represented by vertical line 10), when the skateboard is at rest on the ground, i.e. in the position shown. The steering head axis is represented by line 31.

The king-pin axis 9 extends between the flexibly-located upper and lower portions 17a, 17b.


Figure 1

THIS PAGE BLANK (UJPTG)



THIS PAGE BLANK (USPTO)

Fig. 2



2/4





Fig. 3

THIS PAGE BLANK (USPTO)



3/4

Fig. 4.

THIS PAGE BLANK (USPTO)




Fig. 5.




Fig. 7.



Fig. 9.




Fig. 11.

THIS PAGE BLANK (USPTO)